

FIG. 2A




FIG. 2B




FIG. 2C




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4A

101a

A

D

101b

FIG. 4B




FIG. 4C




FIG. 5A







FIG. 5B














FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9A




FIG. 9B




FIG. 10A





FIG. 10B






FIG. 11A




FIG. 11B




FIG. 12A






FIG. 12B








FIG. 1

FIG. 14A




FIG. 14B




FIG. 14C




FIG. 15A




FIG. 15B





FIG. 16






FIG. 18A







FIG. 18B





-1G. <u>1</u>

FIG. 20A







FIG. 21A

FIG. 21B








FIG. 21C

FIG. 21D









FIG. 22

FIG. 23






FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30A FIG. 30B - 800 - 801 850 { 800 ETL/EIL **~802** 850-C 860 **EML** ~803 ETL/EIL -802 **√804** 860 HIL/HTL **EML ~803** 870 **805 -804** HIL/HTL **- 806** 870-**~ 807** FIG. 30C FIG. 30D 807 850 **806** HTL/HIL 804 **805** 850 { 860-**EML 803**

~ 802

801

800

860-

870

EIL/ETL

870-

HTL/HIL

EML

EIL/ETL

804

803

801

800

~802

EXPLANATION OF REFERENCE

20: counter substrate, 30: TFT substrate, 32: sealant, 33: liquid crystal, 34: barrier layer, 5 35: marker, 40: control device, 42: image-taking means, 43: head, 45: marker, 50: substrate, 51: compound having low wettability, 52: substance having low wettability, 53: light-absorbing material, 54: discharge device, 55: droplet, 56: light source, 57a: high-wettability region, 57b: high-wettability region, 58: low-wettability region, 59: light, 61: compound having low wettability, 63: light-absorbing material, 64: discharge 10 device, 65: droplet, 66: light, 67a: high-wettability region, 67b: high-wettability region, 68: low-wettability region, 70: mask, 71: low-wettability region; 72a: high-wettability region, 72b: high-wettability region, 73: droplet discharge device, 74: droplet, 75a: pattern, 75b: pattern, 100: substrate, 101a: compound having low wettability, 101b: 15 compound having low wettability, 103: gate electrode layer, 104: gate electrode layer, 106: gate insulating layer, 107: semiconductor layer, 108: semiconductor layer, 111: source/drain electrode layer, 112: source/drain electrode layer, 113: source/drain electrode layer, 114: source/drain electrode layer, 117: first electrode layer, 121: insulating layer, 122: electroluminescent layer, 123: second electrode layer, 145: 20 through-hole, 150: low-wettability region, 151a: high-wettability region, 151b: high-wettability region, 152: low-wettability region, 153a: high-wettability region, 153b: high-wettability region, 160: connection wiring layer, 161: connection wiring layer, 162: connection wiring layer, 163: connection wiring layer, 170a: light source, 170b: light source, 171a: light, 171b: light, 180a: droplet discharge device, 180b: droplet discharge device, 300: substrate, 301: high-wettability region, 25 low-wettability region, 302b: low-wettability region, 303: gate electrode layer, 305: gate insulating layer, 306: semiconductor layer, 307: n-type semiconductor layer, 308: source/drain electrode layer, 311: pixel electrode layer, 312: insulating layer, 320: liquid crystal layer, 321: insulating layer, 322: coloring layer, 323: conductive layer, 324: counter substrate, 325: polarizing plate, 330: source/drain electrode layer, 345: 30

5

10

15

20

25

30

through-hole, 350: compound having low wettability, 370: light source, 371: light, 381: droplet discharge device, 401: TFT, 402: capacitor element, 403: TFT, 404: TFT, 405: light emitting element, 406: TFT, 410: signal line, 411: power supply line, 412: power supply line, 413: power supply line, 414: scanning line, 415: power supply line, 416: scanning line, 441: TFT, 442: capacitor element, 443: TFT, 444: light emitting element, 445: TFT, 450: signal line, 451: power supply line, 452: power supply line, 453: scanning line, 454: scanning line, 460: substrate, 461: thin film transistor, 462: source/drain electrode layer, 463: first electrode layer, 464: electroluminescent layer, 465: second electrode layer, 470: substrate, 471: thin film transistor, 472: first electrode layer, 473: electroluminescent layer, 474: second electrode layer, 477: source/drain electrode layer, 478: insulating layer, 480: substrate, 481: thin film transistor, 484: first electrode layer, 485: electroluminescent layer, 486: second electrode layer: 487: source/drain electrode layer, 490: substance including light-absorbing material, 491: low-wettability region, 492a: high-wettability region, 492b: high-wettability region, 493: gate electrode layer, 494: semiconductor layer, 495: n-type semiconductor layer, 496: channel protective layer, 497: gate insulating layer, 498: insulating layer, 500: block, 501: TFT, 502: TFT, 503: light emitting element, 504: capacitor element, 505: source/drain wiring layer, 554: common potential line, 555:common potential line, 561: protective diode, 562: protective diode, 601: TFT, 901: buffer circuit, 902: pixel, 1400: substrate, 1403: droplet discharge means, 1404: image-taking means, 1405: head, 1407: control means, 1408: storage medium, 1409: image processing means, 1410: computer, 1411: marker, 1412: head, 2001: chassis, 2002: display panel, 2003: main screen, 2004: modem, 2005: receiver, 2006: remote control device, 2007: display portion, 2008: sub-screen, 2009; speaker portion, 2010; chassis, 2011; display portion, 2012; keyboard portion, 2013: speaker portion, 2101: main body, 2102: chassis, 2103: display portion, 2104: keyboard, 2105: external connection port, 2106: pointing mouse, 2201: main body, 2202: chassis, 2203: display portion A, 2204: display portion B, 2205: recording medium (such as a DVD) reading portion, 2206: operation keys, 2207: speaker portion,

2301: main body, 2302: audio output portion, 2303: audio input portion, 2304: display portion, 2305: operation switches, 2306: antenna, 2401: main body, 2402: display portion, 2403: chassis, 2404: external connection port, 2405: remote control receiving portion, 2406: receiving portion, 2407: battery, 2408: audio input portion, 2409: eyepiece portion, 2410: operation keys, 2600: TFT substrate, 2601: counter substrate, 2602: sealant, 2603: pixel portion, 2604: liquid crystal layer, 2605: coloring layer, 2606: polarizing plate, 2607: polarizing plate, 2608: driver circuit, 2609: flexible wiring substrate, 2610: cold cathode tube, 2611: reflection plate, 2612: circuit substrate, 2613: optical film, 2700: substrate, 2701: pixel portion, 2702: pixel, 2703: scanning line input terminal, 2704: signal line input terminal, 2750: FPC, 2751: driver IC, 2800: TFT substrate, 2801: protective circuit portion, 2802: TFT, 2803: TFT, 2804: light emitting element, 2805: light emitting element, 2806a: spacer, 2806b: spacer, 2807a: coloring layer, 2807b: coloring layer, 2807c: coloring layer, 2809: driving circuit, 2810: wiring substrate, 2812: heat sink, 2813: heat pipe, 2820: sealing substrate, 3300: element substrate, 3301: pixel portion, 3302: pixel, 3303: sealant, 3304a: desiccant, 3304b: desiccant, 3305: desiccant, 3306a: gate wiring layer, 3306b: gate wiring layer, 3307: filler, 3308: source wiring layer, 3310: sealing substrate, 3350: FPC, 3351: driver IC, 3601: anti-reflective film, 3602: polarizing plate, 3603: retardation film, 3604: retardation film, 3605: insulating layer, 3700: substrate, 3701: pixel portion, 3702: scanning line driver circuit, 3704: signal line input terminal, 4700: substrate, 4701: pixel portion, 4702: scanning line driver circuit, 4704: signal line driver circuit

10

15

20